

Glass Touch T12/T6R/T6

Technical Specifications & Options

L x W x H:
Glass Touch T6
80 x 80 x 11 mm /
3.15 x 3.15 x 0.43 inch
Glass Touch T6R & T12
80 x 160 x 11 mm /
3.15 x 6.3 x 0.43 inch

Weight:
Glass Touch T6
0.11 kg / 0.22 lbs
Glass Touch T6R, T12
0.3 kg / 0.66 lbs

Power Input:
24 VDC, 16 mA (via e:bus)


System Link: e:bus

Control: IR control

Mounting: In-wall mounting

Glass Touches are a series of User Terminals featuring a sleek design with a glass surface as well as touch-sensitive keys and wheel for user interaction. Designed to work with the Butler XT2 via the e:bus protocol, the Glass Touch keys and wheel are easily customized using the e:cue software to perform any function according to project requirements. Pleasing to the eye, these devices are the perfect solution for user interaction and control in high-end lighting applications such as hospitality, architectural, healthcare, residential, and other projects. Glass Touches are wall mountable, and up to eight units can be connected to a single Butler XT2 for flexible installation.

- Sleek glass surface with modern, elegant design
- Touch-sensitive keys and wheel
- Only two wires for power and data (e:bus)
- Easy set up and individual programming options
- Wall mountable, Compatible to standard in-wall fittings



Glass Touch T12



Glass Touch T6



Glass Touch T6R

Action Pad Apps

- For use with any wireless iOS or Android™ device¹
- Allows seamless access to the customizable graphics user interface (GUI) and its Action Pad features (stored inside the Butler XT2 for standalone mode)
- User-friendly, free download
- Updated version, with various new features and graphical enhancements, will be available end 2014



¹ iOS and iTunes are trademark of Apple Inc., registered in the U.S. and other countries. Android and Google Play are trademarks of Google Inc.